


Impact area dimensions



Permissible impact attenuating surface

- Bark grain size 20 do 80mm, min. depth200
- Woodchip grain size 5 do 30 mm, min. depth 200mm
- Sand grain size 0,2 do 2 mm, min. depth 200mm
- Gravel grain size 2 do 8 mm, min. depth 200 mm
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area.

A loose-fill safety surface shall be 100mm thicker than min. depth indicated above.

Technical description

- All posts made of closed profiles 100x100x3mm
- Bars made of Ø33,7x4mm pipes
- Gymnastic rings made of stainless steel pipe Ø30x2mm and armed rope Ø16mm
- Exercise pole and push-up bars made of pipe Ø48,3x2,9mm
- Seat of the exercise bench made of 15mm HDPE sheet
- All steel elements are hot-dip galvanized and painted with an acrylic, structured lacquer
- The set includes foundations made of concrete class C25/30
- All posts shall be set in concrete class C16/20



Components of the Set

- Exercise bench with small ladder-1 pc. •
- Triple parallel bars 1 set ٠
- Double parallel bars 1 set •
- Ladder 1 pc. •
- Horizontal ladder 1 pc. •
- Horizontal snake ladder 1 pc. •
- Exercise pole 2 pcs. •
- Gymnastic rings 1 set •
- Push-up bars 1 set •
- Pull-up bar 7 pcs. •

Product visualization





