



(length x width) 8,00 x 7,5 Free zone: 47.0 m²

Product dimensions



Impact area dimensions



Permissible impact attenuating surface

- Bark grain size 20 do 80mm, min. depth200
- Woodchip grain size 5 do 30 mm, min. depth 200mm
- Sand grain size 0,2 do 2 mm, min. depth 200mm
- Gravel grain size 2 do 8 mm, min. depth 200 mm
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area. A loose-fill safety surface shall be 100mm thicker than min.

depth indicated above.

Technical description

- All posts made of closed profiles 100x100x3mm
- Bars made of Ø33,7x4mm pipes
- Gymnastic rings made of stainless steel pipe Ø30x2mm and armed rope Ø16mm
- Exercise pole made of Ø38x4mm pipe
- Horizontal ladder made of Ø33,7x4mm and Ø38x4mm pipes
- All steel elements are hot-dip galvanized and painted with an acrylic, structured lacquer
- The set includes foundations made of concrete class C25/30
- All posts shall be set in concrete class C16/20



```
Components of the Set
```

- Double parallel bars- 1 set
- Horizontal ladder 1 pc.
- Slanted ladder 1 pc.
- Exercise pole 1 pc.
- Gymnastic rings 1 set
- Pull-up bar 3 pcs.

Product visualization

