

- Woodchip grain size 5 do 30 mm, min. depth 200mm
- Sand grain size 0,2 do 2 mm, min. depth 200mm
- Gravel grain size 2 do 8 mm, min. depth 200 mm
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area.

A loose-fill safety surface shall be 100mm thicker than min. depth indicated above.

Technical description

All posts made of closed profiles 100x100x3mm •

nn

- Bars and ladders made of pipes: ø33,7x4mm and Ø38x4mm
- Horizontal snake ladder made of pipes: Ø42x4x2,9 and Ø38x2,6mm, •
- Ø40mm jute climbing rope
- Gymnastic rings made of stainless steel pipe Ø30x2mm and armed rope Ø16mm •
- Push-up bars made of ø48,3x2,9mm pipes •
- Seats of the exercise benches made of 15mm HDPE sheets •
- All steel elements are hot-dip galvanized and painted with an acrylic, structured lacquer •
- The set includes foundations made of concrete class C25/30 •
- All posts shall be set in concrete class C16/20



Components of the Set

- Push-up bars 1set
- Triple parallel bars 1set
- Double parallel bars 1set
- Exercise bench with small ladder 1pc.
- Horizontal snake ladder 1pc.
- Horizontal ladder 1pc.
- Ladder 1pc.
- Gymnastic rings 1set
- Climbing rope 1pc.
- Pull-up bar 14pcs.

Product visualization

