


STREET WORKOUT SET NO. 34


Catalogue number: 88034

It shall apply from: 22-01-2024


Max. free fall height:	2,80 m
Product Dimensions: (length x width x height)	8,22 x 6,75 x 3,90 m
Impact area: (length x width)	12,00 x 10,55 m
Free zone:	92,0 m ²



Product dimensions



Impact area dimensions



Permissible impact attenuating surface

- Bark – grain size 20 do 80mm, min. depth 200
- Woodchip – grain size 5 do 30 mm, min. depth 200mm
- Sand – grain size 0,2 do 2 mm, min. depth 200mm
- Gravel – grain size 2 do 8 mm, min. depth 200 mm
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area.

A loose-fill safety surface shall be 100mm thicker than min. depth indicated above.

Technical description

- All posts made of closed profiles 100x100x3mm
- Bars made of Ø33,7x4mm pipes
- Horizontal and slanted ladders made of pipes: Ø38x4mm and Ø33,7x4mm,
- Gymnastic rings made of stainless steel pipe Ø30x2mm and armed rope Ø16mm
- Push-up bars and parallel bars made of Ø48,3x2,9mm pipes
- Seat of the exercise bench made of 15mm HDPE sheet
- Exercise pole made of Ø48,3x2,9mm pipe
- All steel elements are hot-dip galvanized and painted with an acrylic, structured lacquer
- The set includes foundations made of concrete class C25/30
- All posts shall be set in concrete class C16/20

TECHNICAL DATA SHEET

Product visualization

