


TECHNICAL DATA SHEET


STREET WORKOUT SET NO. 18

Catalogue number: 88018

It shall apply from: 25-03-2025	
Max. free fall height:	1,30 m
Product Dimensions: (length x width x height)	5,67 x 5,18 x 3,90 m
Impact area: (length x width)	8,63 x 8,18 m
Free zone:	52 m ²



Product dimensions



Impact area dimensions

8629 5664 572

Permissible impact attenuating surface

- Bark grain size 20 do 80mm, min. depth200
- Woodchip grain size 5 do 30 mm, min. depth 200mm
- Sand grain size 0,2 do 2 mm, min. depth 200mm
- Gravel grain size 2 do 8 mm, min. depth 200 mm
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area.

A loose-fill safety surface shall be 100mm thicker than min. depth indicated above.

Technical description

- All posts made of closed profiles 100x100x3mm
- Bars and ladders made of Ø33,7x4mm pipes
- Gymnastic rings made of stainless steel pipe Ø30x2mm and armed rope Ø16mm
- Low parallel bars made of Ø48,3x2,9mm pipe
- Seat of the exercise bench made of 15mm HDPE sheet
- Horizontal ladder made of pipes: Ø38x4mm and Ø33,7x4mm
- Parallel bars made of Ø38x4mm pipe
- All steel elements are hot-dip galvanized and painted with an acrylic, structured lacquer
- The set includes foundations made of concrete class C25/30
- All posts shall be set in concrete class C16/20



TECHNICAL DATA SHEET

Components of the Set

- Gymnastic rings 1set
- Horizontal ladder 1pc.
- Ladder 1pc.
- Parallel bars 1set
- Exercise bench with small ladder 1pc.
- Push-up bars-1set
- Pull-up bar 1pc.

Product visualization



