

e-mail: marketing@muller.com.pl tel. 071 318 84 84, fax 071 318 84 83

TECHNICAL DATA SHEET


AVENIR PLAYGROUND SET 3

Catalogue number: 72003

It shall apply from: 2025-01-09	
Max. free fall height:	1,38 m
Product Dimensions: (length x width x height)	3,64 x 0,76 x 2,23 m
Impact area: (length x width)	7,11 x 3,71 m



Impact area dimensions



Permissible impact attenuating surface

- Bark grain size 20 do 80 mm, min. depth 200 mm + 100mm (for displacement)
- Woodchip grain size 5 do 30 mm, min. depth 200mm + 100mm (for displacement)
- Sand grain size 0,2 do 2 mm, min. depth 200mm + 100mm (for displacement)
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area. A loose surface should be made so that its thickness is 100 mm greater than the minimum value given above.

Technical description

- Construction made of steel pipes Ø48,3×2,9mm,
- Surface elements made of 8mm thick HPL boards
- Floor platforms made of anti-slip, waterproof plywood, 21mm thick,
- Slide made of stainless steel and HDPE board 19mm thick
- Rope elements made of reinforced rope Ø16mm
- The steel structure is hot-dip galvanized and powder-coated,
- The set includes foundations made of concrete of class C25/30.

List of components

- Rope ladder H1350 x1szt
- Climbing entrance with rope H1350 x1szt
- Crossbar H1350 x4szt
- Necking H1350 x1szt
- Ladder H1350 (Z) x1szt
- Slide H1350 x1szt
- Tower W4-1350-BD x1szt



Product visualization

