

## AVENIR PLAYGROUND SET 6


Catalogue number: 72006

It shall apply from: 2025-01-10

<b>Max. free fall height:</b>	1,38 m
<b>Product Dimensions:</b> (length x width x height)	3,63 x 3,47 x 3,02 m
<b>Impact area:</b> (length x width)	6,48 x 6,41 m



### Impact area dimensions



### Permissible impact attenuating surface

- Bark – grain size 20 do 80 mm, min. depth 200 mm + 100mm (for displacement)
- Woodchip – grain size 5 do 30 mm, min. depth 200mm + 100mm (for displacement)
- Sand – grain size 0,2 do 2 mm, min. depth 200mm + 100mm (for displacement)
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

*The impact attenuating surfacing shall be installed on the whole of impact area.*

*A loose surface should be made so that its thickness is 100 mm greater than the minimum value given above.*

### Technical description

- Construction made of steel pipes  $\varnothing 48,3 \times 2,9$ mm,
- Surface elements made of 8mm thick HPL boards
- Floor platforms made of anti-slip, waterproof plywood, 21mm thick,
- Steps made of anti-slip HDPE board
- Slide made of stainless steel and HDPE board 19mm thick
- Rope elements made of reinforced rope  $\varnothing 16$ mm
- The steel structure is hot-dip galvanized and powder-coated,
- The set includes foundations made of concrete of class C25/30.

## TECHNICAL DATA SHEET

### List of component

- Arch ladder H1350 x1pcs
- Climbing entrance with rope H1350 x1pc
- Rope bridge with steps L1320 H1350 x1pc
- Crossbar H1350 x4pcs
- Necking H1350 x1pcs
- Tower W4-1350-ZD4 x1pc
- Firemen's pipe H1350 x1pc
- Slide H1350 x1pc
- Slanted rope ladder H1350 x1pc
- Climbing entrance H1350 (M) x1pc
- Tower W4-1350-BD x1pc
- Roof D4 x1pc

### Product visualization

