


## **AVENIR PLAYGROUND SET 8**

Catalogue number: 72008





Permissible impact attenuating surface

- Bark grain size 20 do 80 mm, min. depth 200 mm + 100mm (for displacement)
- Woodchip grain size 5 do 30 mm, min. depth 200mm + 100mm (for displacement)
- Sand grain size 0,2 do 2 mm, min. depth 200mm + 100mm (for displacement)
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area.

A loose surface should be made so that its thickness is 100 mm greater than the minimum value given above.

## **Technical description**

- Construction made of steel pipes Ø48,3x2,9mm, •
- Surface elements made of 8mm thick HPL boards decorated with colourful prints resistant to UV radiation
- Slide made of stainless steel and milled HPL board 10mm thick
- Rope elements made of reinforced rope Ø16mm,
- The steel structure is hot-dip galvanized and powder-coated,
- The set includes foundations made of concrete of class C25/30. •

## **List of components**

- Tower W4-950-ZD1 x2pcs ٠
- Arch ladder H950 x1pc
- Spider Web Climber x1pc
- Rope ladder H950 x1pc
- Roof D1 (MB) x2pcs
- Rope bridge L1320 H950 x1pc •
- Necking H950 x1pc
- Crossbar H950 x5pcs
- Slide H950 x1pc •



**Product visualization** 

