


TECHNICAL DATA SHEET

AVENIR PLAYGROUND SET 14


Catalogue number: 72014

It shall apply from: 2025-01-13

Max. free fall height:	1,11 m
Product Dimensions: (length x width x height)	4,71 x 3,39 x 1,83 m
Impact area: (length x width)	7,67 x 6,36 m



Impact area dimensions



Permissible impact attenuating surface

- Bark – grain size 20 do 80 mm, min. depth 200 mm + 100mm (for displacement)
- Woodchip – grain size 5 do 30 mm, min. depth 200mm + 100mm (for displacement)
- Sand – grain size 0,2 do 2 mm, min. depth 200mm + 100mm (for displacement)
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

The impact attenuating surfacing shall be installed on the whole of impact area.

A loose surface should be made so that its thickness is 100 mm greater than the minimum value given above.

Technical description

- Construction made of steel pipes $\varnothing 48,3 \times 2,9$ mm,
- Surface elements made of 8mm thick HPL boards
- Floor platforms made of anti-slip, waterproof plywood, 21mm thick,
- Steps made of anti-slip HDPE board
- Slide made of stainless steel and HDPE board 19mm thick
- Rope elements made of reinforced rope $\varnothing 16$ mm
- The steel structure is hot-dip galvanized and powder-coated,
- The set includes foundations made of concrete of class C25/30.

TECHNICAL DATA SHEET

List of components

- Tower H-150 x2szt
- Tower H-550 x1szt
- Tower W3-150-BD x1szt
- Crossbar H550 x1szt
- Stepping pads L1320 H150 x1szt
- Crossbar W3 H150 x1szt
- Tower W4-150-BD x1szt
- Tunnel L660 H150 x1szt
- Tower W4-550-BD x1szt
- Tunnel L660 H950 x1szt
- Slanted bridge L660 H550-950 x2szt
- Balance beam L1320 H550 x1szt
- Rope net bridge L660 H550 x1szt
- Slide H550 x1szt
- Tower H-950 x2szt
- Crossbar H150 x2szt
- Slanted rope net bridge L660 H150-550 x1szt
- Tower W3-550-BD x2szt
- Stairs H550 (MB) x1szt

Product visualization

