


## STREET WORKOUT SET NO. 11


Catalogue number: 88011

It shall apply from: 22-01-2024


<b>Max. free fall height:</b>	2,40 m
<b>Product Dimensions:</b> (length x width x height)	8,84 x 5,38 x 3,5 m
<b>Impact area:</b> (length x width)	12,10 x 8,91 m
<b>Free zone:</b>	84,3 m <sup>2</sup>



### Product dimensions



### Impact area dimensions



### Permissible impact attenuating surface

- Bark – grain size 20 do 80mm, min. depth 200
- Woodchip – grain size 5 do 30 mm, min. depth 200mm
- Sand – grain size 0,2 do 2 mm, min. depth 200mm
- Gravel – grain size 2 do 8 mm, min. depth 200 mm
- Synthetic surfaces in accordance whit tested HIC (EN 1177)

*The impact attenuating surfacing shall be installed on the whole of impact area.  
A loose-fill safety surface shall be 100mm thicker than min. depth indicated above.*

### Technical description

- All posts made of closed profiles 100x100x3mm
- Construction made of pipes:  $\varnothing 33,7 \times 4$ mm,  $\varnothing 38 \times 4$ mm and  $\varnothing 48,3 \times 2,9$ mm
- Log roll made of  $\varnothing 133 \times 4$ mm pipe and lined with planks
- Gymnastic rings made of stainless steel pipe  $\varnothing 30 \times 2$ mm and armed rope  $\varnothing 16$ mm
- All steel elements are hot-dip galvanized and painted with an acrylic, structured lacquer
- The set includes foundations made of concrete class C25/30
- All posts shall be set in concrete class C16/20

### Components of the Set

## TECHNICAL DATA SHEET

- Exercise bench with small ladder – 2 pcs.
- Parallel bar – 3 pcs.
- Slanted bar – 1 pc.
- Exercise pole – 1 pc.
- Gymnastic rings – 1 set
- Log roll – 1 pc.
- Push-up bar – 2 pcs.
- Horizontal snake ladder – 1 pc.
- Pull-up bar – 4 pcs.

### Product visualization

